



Stainless Steel SS304 SS316 Cam Lock Pipe Fittings Aluminum

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-QC-15
- Minimum Order Quantity: 10PCS
- Price: USD2-USD25 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



Product Specification

- Highlight: **SS316 cam lock pipe fittings,
SS304 cam lock pipe fittings,
Aluminum 6 camlock fittings**

for more products please visit us on piping-industry.com

Product Description

Aluminium Stainless Steel SS304 SS316 Camlock Couplings Quick Couplings Factory

Camlock couplings are well-known as quick hose coupling providing quick connection and disconnection for pumps, tanks, equipment, Stainless steel cam lock fittings allow for quick and secure hose connections. The camlock couplings mate by inserting the grooved coupling into the cam coupling and simply closing the cam or lever arms. Safety pins or locks prevent the cam arms from accidental disconnection during use.

Product Information/Product Description/Basis Information/Specification

Comlock Types:	Type A, Type B, Type C, Type D, Type E, Type F, Type DC, Type DP, Type DW
Sizes	1/2", 3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2", 3", 4", 5", 6" 8"10" 12"
Working Pressure	5 kg/cm2 to 20 kg/cm2 (working varies according to the size of coupling)
Material	Aluminium, Bronze, Carbon Steel, S.S.304, S.S.316 PP / Cement, Fertilizers, Fire Fighting Equipment, Ink / Dye /
Application	Paint Industries , Petrochemical / Refineries / Process Industries, Mining, Oil Drilling Companies
	(offshore / onshore), Railways, Steel Plants, Military, Applications, Pneumatic Conveyors, Oil Blending Plants,
	Automobile manufacturers, Chemical Industries and Furnaces.

Features /Advantages:

1. Simple structure, convenient operation, quick connect and open it
2. compact size, light weight, good sealing and interchangeability
3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium
4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc
5. Cam & groove couplings are easy to operate. Camlock consists of two parts - male adaptor and female coupler. You just need insert the adaptor into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power
6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications

Types of the cam & groove couplings



316 SS Camlock quick coupling
Male camlock adaptor inner thread



316 SS Camlock coupler
Female camlock coupler outer thread

Type A

Size:	Product no:
1/2"	camlock A50
3/4"	camlock A75
1"	camlock A100
1 1/4"	camlock A125
1 1/2"	camlock A150
2"	camlock A200
2 1/2"	camlock A250
3"	camlock A300
4"	camlock A400
5"	camlock A500
6"	camlock A600

Type B

Size:	Product no:
1/2"	camlock B50
3/4"	camlock B75
1"	camlock B100
1 1/4"	camlock B125
1 1/2"	camlock B150
2"	camlock B200
2 1/2"	camlock B250
3"	camlock B300
4"	camlock B400
5"	camlock B500
6"	camlock B600



316 SS Camlock hose tail coupling
Female camlock coupler with serrated hose tail

Type C

Size:	Product no:
1/2"	camlock C50
3/4"	camlock C75
1"	camlock C100
1 1/4"	camlock C125
1 1/2"	camlock C150
2"	camlock C200
2 1/2"	camlock C250
3"	camlock C300
4"	camlock C400
5"	camlock C500
6"	camlock C600



316 SS Camlock lever coupling
Female snaplock coupler inner thread

Type D

Size:	Product no:
1/2"	camlock D50
3/4"	camlock D75
1"	camlock D100
1 1/4"	camlock D125
1 1/2"	camlock D150
2"	camlock D200
2 1/2"	camlock D250
3"	camlock D300
4"	camlock D400
5"	camlock D500
6"	camlock D600



316 SS Camlock hose tail coupling
Male camlock adaptor hose connection

Type E

Size:	Product no:
1/2"	camlock E50
3/4"	camlock E75
1"	camlock E100
1 1/4"	camlock E125
1 1/2"	camlock E150
2"	camlock E200
2 1/2"	camlock E250
3"	camlock E300
4"	camlock E400
5"	camlock E500
6"	camlock E600



316 SS Camlock quick coupling
Male camlock adaptor outer thread

Type F

Size:	Product no:
1/2"	camlock F50
3/4"	camlock F75
1"	camlock F100
1 1/4"	camlock F125
1 1/2"	camlock F150
2"	camlock F200
2 1/2"	camlock F250
3"	camlock F300
4"	camlock F400
5"	camlock F500
6"	camlock F600



316 INOX Camlock Dustplug

Type DP

Size:	Product no:
1/2"	camlock DP50
3/4"	camlock DP75
1"	camlock DP100
1 1/4"	camlock DP125
1 1/2"	camlock DP150
2"	camlock DP200
2 1/2"	camlock DP250
3"	camlock DP300
4"	camlock DP400
5"	camlock DP500
6"	camlock DP600



316 INOX Camlock Dust cap

Type DC

Size:	Product no:
1/2"	camlock DC50
3/4"	camlock DC75
1"	camlock DC100
1 1/4"	camlock DC125
1 1/2"	camlock DC150
2"	camlock DC200
2 1/2"	camlock DC250
3"	camlock DC300
4"	camlock DC400
5"	camlock DC500
6"	camlock DC600

Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

Our Service

1. Technical support
2. Raw Material Quality control.
3. Inspection during the production time.
4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
5. Test Report each shipment
4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
5. Flexible payment Ways: LC. TT. DP
6. Customized Package includes Logo. Cases Dimension.
7. 18 months quality Guarantee time.
9. Free replacement by air if any error founded
10. 24 hours to Feedback your questions

DEYE SHIJIAZHANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)

+8613292824811 sales@deyepiping.com piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China