# PN16 PN10 Cast Ductile Iron Foot Check Valve With Stainless Steel Screen

## **Basic Information**

Place of Origin: CHINABrand Name: DEYE

Certification: ISO9001:2015 PED
 Model Number: DY-CV-R-01
 Minimum Order Quantity: 10PCS

• Price: USD2-USD20000 each

Packaging Details: carton box+ ply wooden cases or carton+

Pallets

• Delivery Time: 20 days for usual order, 7 days for stocked

items

Payment Terms: T/T, L/C, D/P
Supply Ability: 1000pcs one month



# **Product Specification**

Highlight: PN10 foot check valve, PN16 foot check valve,
 Cast Ductile Iron foot check valves



# More Images





## **Product Description**

Model No. CV-R-01

Ductile iron/cast iron foot check valves with NBR seat, stainless steel strainer, PN10/PN16/150LBS. Temperature: -0 -+80

#### **Quick Detail**

Design standard: DIN/BS Pressure: DIN PN16 Working temperature: 0 ~+80. Test and inspection: EN12266-1

Connection: Flange ends conform to EN1092-1 Epoxy Powder Coated inside and outside

#### **Product Range:**

Available Body Material: Cast Iron GG25, Ductile iron GGG40, GGG50

Optional Seat Ring: NBR, EPDM Optional Ends: BS4504/EN1092-1 PN16 Size Range: DN50-DN250 (2"-10") Pressure Range: PN10, PN16

Optional surface color: RAL5002, RAL5015. RAL5005, red, black. Or customized

#### Performance:

- 1. The foot valve is a kind of energy-saving valve.
- 2. Generally installed at the bottom end of the underwater suction pipe of the pump to restrict the liquid in the pump pipe from returning to the water source.
- 3. There are many water inlets and reinforcing ribs on the bonnet, which are not easy to block, and are mainly used in pumping pipelines. T
- Coated with fusion bonded epoxy Min. 250 microns.

#### **Technical data sheets**

### Application:

Water, oil, and non-corrosive media

# SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China

